Stationary 2-pump high pressure washers for heavy cleaning tasks







* EPP = Expanded PolyPropyleneas



Maximised cleaning efficiency

The SC DUO models 6P and 7P significantly improve the performance levels of 2-pump cold water high pressure washers. Thanks to higher working pressure and increased water flow, even large heavy-duty cleaning jobs can be handled with ease.

Offers you the flexibility of being either one user – or two working together. Cleaning efficiency is maximized by a 4-piston long-life motor pump accepting both cold and hot water up to 85°C.

Designed for large cleaning tasks SC DUO 6P & 7P are ideal for agriculture with milking sheds, sties, and stables. Food and pharma industry with processing equipment, conveyors, and tanks. Shipping and industry with ship decks, bulkheads, and industrial equipment. Even oil and grease can be removed thanks to the hot water inlet and mountable options as 2 x high pressure detergent.

Built for use in excess of 6 hours per day, each model can be customized to meet your exact cleaning needs and ensure a lower Total Cost of Ownership.

Powered by quality

- NA6 and C3 high-quality motor pumps with brass pump heads
- 1450 rpm; 4 full ceramic pistons and double roller bearings
- Working pressure up to 200 bar
- Water flow up to 5000 l/h
- 70°-85°C hot water inlet for max. cleaning efficiency

Innovative hard foam cabinet

- Newly developed hard foam cabinet* approved for the food industry also reduces the noise level
- Built on powder-coated steel frame

Customized for lower TCO

- Choose a basic or more feature packed model to achieve low Total Cost of Ownership.
- Extra optional features include, stainless steel frame and cabinet, high pressure detergent injector, remote control, Low water inlet security, Accessory Storage Kit and low water security.
- Optional add-ons to fulfill EU norm 1717: Water Break Tank or BA valve



Accessory storage kit.



External Water Break Tank for op til 40 ltr/min.



Cabinet can be removed quickly for direct access to the motor pump.



Pump oil tank with oil level sight and fill/empty function.

More productive: Increased working pressure and water flow for faster cleaning

- Flexible: High reconfigurability, customization with optional equipment to meet specific needs
- Innovative hard foam cabinet: Approved for use within the food sector.
- •Solid: Built on powder-coated steel frame
- Ease-of-use: Accessory kit for immediate plug and play use.
- Convenient: Intelligent start-stop function for motor pump, reducing wear and tear on pump elements
- Time-saving maintenance: Easy access to motor pump and other vital parts





TECHNICAL SPECIFICATIONS

Description	SC DUO 6P-170/3220	SC DUO 7P-180/2400
Item no.	107340600	107340620
Pump pressure (bar/MPa)	170/17	180/18
Cleaning impact (kg/force)	15.8	12.1
Water flow Qmax/Qiec (l/h)	3220/3000	2400/2240
Max. inlet temperature (°C)	85	85
Number of pumps	2	2
Pump (RPM)	1450	1450
Dimensions L x W x H (mm)	355x860x1000	355x860x1000
Weight (kg)	180	160
Power consumption (kW)	18.0	16.4
Voltage/phase/frequency/current (V/~/Hz/A)	400/3/50/32	400/3/50/27
El cable (m)	5	5
Nozzle size	.0900	.0640
Features:		
Pistons / number of pistons	Ceramic / 4	Ceramic / 4
Automatic start/stop	•	•
Hour counter	•	•
Service warning lamp	•	•
Standard equipment:		
Ergo coupling	101119496	101119496
Water inlet coupling	1602945	1602945

Nilfisk A/S Kornmarksvej 1 · DK-2605 Brøndby · Denmark Tel.: +45 43 23 81 00 · Fax: +45 43 43 77 00 mail.com@nilfisk.com www.nilfisk.com

