Range of industrial vacuums - made to be strong





Superior suction power in a strong and flexible solution

ATTIX 115, 125, 145 & 155 are designed to answer the market request for solutions in industrial vacuuming for the manufacturing and heavy industry world. The machines are ideal for liquids and solid materials with a performance to perfectly satisfy any cleaning and maintenance situation.

Equipped with either three powerful by-pass motors or a silent and reliable side-channel blower all machines integrate a durable high filtration star-filter (L- or M-Class) with big surface area. The manual filter shaker on top of the machine is easy-to-use and ensures a high efficiency of the filter. With the 100 liters bin capacity ATTIX 115, 125, 145 & 155 are ideal for heavy industrial vacuum cleaning in construction sites, mechanical, ceramics, food and chemical industries.

- SitDown container with castors and handle for a practical material disposal
- Accessory box, cable and hose holders for a functional vac
- Double stage side-channel blower connected in parallel for a highest airflow (ATTIX 155)
- Plug with phase inverter that is easy to use when the phases are inverted
- Optional EasyDisposal kit with plastic bag for a quick and safe material disposal
- Optional H14 HEPA Upstream absolute filter for fine dust filtration





The serie of industrial vacuum cleaners is the ideal solution for demanding applications in industry and construction sites where high airflow is required. The all-steel construction secures a strong and reliable machine with high mobility and big capacity.



The wet & dry machines integrate a durable polyester star-filter with large surface area – suitable for fine dust applications. A build-in manometer in ATTIX 145/155 monitors the filter efficiency during use.

ATTIX 115 & 125



ATTIX 145 & 155



Ideal for heavy industrial vacuum cleaning





TECHNICAL DATA

Description	ATTIX 115-01	ATTIX 125-01	ATTIX 145-01	ATTIX 155-01
Item no.	4010500044	4010500045	4030500151	4030800366
Air flow rate (I/min.)	8100	8100	5250	5250
Vacuum (mbar/kPa)	230/23	230/23	300/30	300/30
Power Piec (W)	3 x 1000	3 x 1000	2200	4000
Working sound level (dB(A))	71	71	68	72
Container volume (I)	100	100	100	100
Mains connection (V/~/Hz)	230/1/50-60	230/1/50-60	400/3/50	400/3/50
Dimensions L x W x H (mm)	800 x 600 x 1555	800 x 600 x 1555	1130 x 600 x 1530	1130 x 600 x 1530
Weight (kg)	68	73	114	139
El cable (m)	9	9	9	9
Main filter type	PET Starfilter	PET Starfilter	PET Starfilter	PET Starfilter
Filter cleaning system	Manual filter shaker	Manual filter shaker	Manual filter shaker	Manual filter shaker
Features:				
AntiStatic system	•	•	•	•
Release container system	•	•	•	•
Chassis on wheels with brakes	•	•	•	•
Independent motor/switches	•	•		
L-class filter	•		•	•
M-class filter		•		
Manometer			•	•
Plug with phase inverter			•	•
Three phase side chanel blower			•	•
Standard equipment:				
Kit star filter D460 L-class	40000338		40000338	40000338
18 pocket start filter kit M-class		40000699		
Adaptor D70 CFM – D60 MultiFit	4072200392	4072200392	4072200392	4072200392
Small basket object kit with nuts bolts		40000892		
Removable cyclone D460 FE complete big	Z5 60109			

